


ONE-TOUCH FITTINGS

> METRIC SYSTEM

PC male straight




MODEL	ØD	T (Thread)	L	A	B	H1	H2	ØP	ORIFICE
PC 04-01	4	PT1/8	20.3	8	15	10	3	10	3
PC 04-02	4	PT1/4	18.4	10	15	14	3	10	3
PC 04-03	4	PT3/8	19	11	15	17	4	10	3
PC 04-M5	4	M5×P0.8	20.1	4	15	10	2	10	2
PC 04-M6	4	M6×P1.0	20.6	4	15	10	2.5	10	3
PC 06-01	6	PT1/8	21	8	15	12	4	12	4
PC 06-02	6	PT1/4	22.8	10	15	14	4	12	4
PC 06-03	6	PT3/8	20.8	11	15	17	4	12	4
PC 06-04	6	PT1/2	24.8	14	15	21	4	12	4
PC 06-M5	6	M5×P0.8	21	4	15	12	2	12	2
PC 06-M6	6	M6×P1.0	21	4	15	12	2.5	12	3
PC 08-01	8	PT1/8	25.4	8	18	14	5	14	5
PC 08-02	8	PT1/4	24.4	10	18	14	6	14	6
PC 08-03	8	PT3/8	21.4	11	18	17	6	14	6
PC 08-04	8	PT1/2	25.4	14	18	21	6	14	6
PC 10-01	10	PT1/8	29.5	8	22	17	5	17	5
PC 10-02	10	PT1/4	31	10	22	17	6	17	6
PC 10-03	10	PT3/8	28.5	11	22	17	8	17	8
PC 10-04	10	PT1/2	26.8	14	22	21	8	17	8
PC 12-01	12	PT1/8	32	8	22	21	5	20	5
PC 12-02	12	PT1/4	34	10	22	21	6	20	6
PC 12-03	12	PT3/8	31	11	22	21	8	20	8
PC 12-04	12	PT1/2	33.5	14	22	21	8	20	8
PC 16-03	16	PT3/8	37.8	11	24	24	8	24	8
PC 16-04	16	PT1/2	39.8	14	24	24	10	24	10

ONE-TOUCH FITTINGS

> INCH SYSTEM

PC male straight




MODEL	ØD	ØP	T (Thread)	L	A	B	H1	H2	ORIFICE
PC 5/32-UNF	5/32	10.5	UNF10/32	21.4	3.6	15	7/16	3/32	2.5
PC 5/32-N01	5/32	10.5	NPT1/8	19.5	8.5	15	7/16	3/32	3.2
PC 5/32-N02	5/32	10.5	NPT1/4	22.0	10.5	15	9/16	1/8	3.2
PC 5/32-N03	5/32	10.5	NPT3/8	23.0	11.5	15	11/16	1/8	3.2
PC 3/16-UNF	3/16	11.0	UNF10/32	22.0	3.6	15	7/16	3/32	2.5
PC 3/16-N01	3/16	11.0	NPT1/8	23.1	8.5	15	7/16	1/8	3.2
PC 3/16-N02	3/16	11.0	NPT1/4	23.1	10.5	15	9/16	1/8	3.2
PC 3/16-N03	3/16	11.0	NPT3/8	24.1	11.5	15	11/16	1/8	3.2
PC 1/4-UNF	1/4	12.7	UNF10/32	23.2	3.6	15	1/2	3/32	2.5
PC 1/4-N01	1/4	12.7	NPT1/8	23.8	8.5	15	1/2	3/16	4.0
PC 1/4-N02	1/4	12.7	NPT1/4	23.2	10.5	15	9/16	3/16	4.0
PC 1/4-N03	1/4	12.7	NPT3/8	24.2	11.5	15	11/16	3/16	4.0
PC 1/4-N04	1/4	12.7	NPT1/2	27.3	14.5	15	7/8	3/16	4.0
PC 5/16-N01	5/16	14.0	NPT1/8	28.2	8.5	18	9/16	3/16	4.8
PC 5/16-N02	5/16	14.0	NPT1/4	26.0	10.5	18	9/16	1/4	6.4
PC 5/16-N03	5/16	14.0	NPT3/8	26.5	11.5	18	11/16	1/4	6.4
PC 5/16-N04	5/16	14.0	NPT1/2	24.5	14.5	18	7/8	1/4	6.4
PC 3/8-N01	3/8	16.7	NPT1/8	30.1	8.5	22	11/16	3/16	4.8
PC 3/8-N02	3/8	16.7	NPT1/4	31.1	10.5	22	11/16	1/4	6.4
PC 3/8-N03	3/8	16.7	NPT3/8	24.8	11.5	22	11/16	5/16	7.9
PC 3/8-N04	3/8	16.7	NPT1/2	24.0	14.5	22	7/8	5/16	7.9
PC 1/2-N01	1/2	20.6	NPT1/8	33.4	8.5	22	7/8	3/16	4.8
PC 1/2-N02	1/2	20.6	NPT1/4	35.4	10.5	22	7/8	1/4	6.4
PC 1/2-N03	1/2	20.6	NPT3/8	31.9	11.5	22	7/8	3/8	9.5
PC 1/2-N04	1/2	20.6	NPT1/2	31.4	14.5	22	7/8	3/8	9.5

ONE-TOUCH FITTINGS / G TYPE

> METRIC SYSTEM, BSPP, WITH INTEGRAL O-RING SEAL

PC male straight



MODEL	ØD	T (Thread)	L (mm)	A (mm)	B	H1 (mm)	H2 (mm)	ORIFICE
PC 04-G01	4	G 1/8	22.1	5.5	15	14	3	3
PC 04-G02	4	G 1/4	21.4	7.5	15	17	3	3
PC 06-G01	6	G 1/8	23.2	5.5	15	14	4	4
PC 06-G02	6	G 1/4	23.5	7.5	15	17	4	4
PC 06-G03	6	G 3/8	20.5	7.5	15	20	4	4
PC 08-G01	8	G 1/8	25.5	5.5	18	14	4	4
PC 08-G02	8	G 1/4	24.5	7.5	18	17	5	5
PC 08-G03	8	G 3/8	21	7.5	18	20	6	6
PC 08-G04	8	G 1/2	24.5	10	18	24	6	6
PC 10-G01	10	G 1/8	29.2	5.5	22	17	4	4
PC 10-G02	10	G 1/4	30.9	7.5	22	17	6	6
PC 10-G03	10	G 3/8	27.2	7.5	22	20	6	6
PC 10-G04	10	G 1/2	30.4	10	22	24	8	8
PC 12-G02	12	G 1/4	33.5	7.5	22	21	6	6
PC 12-G03	12	G 3/8	28.5	7.5	22	21	8	8
PC 12-G04	12	G 1/2	31	10	22	24	8	8
PC 16-G03	16	G 3/8	35.5	7.5	24	24	8	8
PC 16-G04	16	G 1/2	38	10	24	24	10	10