



LS809-31LS Series–Level Sensor

Features

- High or low level sensing
- External fitting
- Reed Switch reliability
- Easy installation

Comments

- High or low level sensing, single pole double throw
- Normally open or normally closed by rotating through 180
- Suitable for a wide range of liquids
- Interface option available
- Polypropylene Material

Applications

- Continuous 80
- Water high or low Level
- Condensate level alarm
- Drinking water level
- Cooling systems

Material

Housing Material Glass Filled Polypropylene
Float Material Glass Filled Polypropylene
Contact Material Ruthenium

Float SG 0.65
Operating Temperature °C -30 to 105
Medium Water
Housing and Float Color Charcoal

Cable

Cable Length2 x 0.5M single insulatedConnection TypeStripped Cables

Cable Type18AWG, 32/0.2mm PVC insulatedCable ColorBlack

Mechanical Specifications

Shock 50g for 11mS duration Vibration 35g up to 500Hz Maximum Pressure 2.0 Bar IP IP65

Mounting

Thread	½" NPT
Fitment	External
Mounting	Horizontal

Switching

Switch Action (Reed Switch)

Max Switching Voltage VDC

Max Switching Voltage VAC

Max Switching Current Amps

Max Switching Load Watt

Operate Mode
Contact Form

SPST

200

250

1

70

N/C with float horizontal

Technical Drawing

POSITION DIRENTATION ROCKATOR POSITION DIRENTATION (1),260 POSIT

NORTH AMERICA & EUROPE

MEAS Deutschland GmbH a TE Connectivity Company Hauert 13 D-44227 Dortmund Germany Phone: +49-(0)231-9740-0 Fax: +49-(0)231-9740-20 Email: info.de@meas-spec.com

ASIA

Measurement Specialties (China), Ltd., a TE Connectivity Company No. 26 Langshan Road Shenzhen High-Tech Park (North) Nanshan District, Shenzhen 518057 China Tel +86 755 3330 5088 Fax +86 755 3330 5099

te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, MEAS, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.