



VS309-51N VS Series-Level Sensor

Features

- High or low level sensing
- Internal or external fitting
- Reed Switch reliability
- Nitrile Sealing washer/grommet
- Easy installation

Comments

- Normally open or normally closed by float inversion
- Suitable for a wide range of liquids
- Interface option available
- Nylon 6.6 Material

Applications

- Chemical high or low level
- Diesel Fuel
- Fuel low level
- Alcohols
- Low Oil Detection

Material

Housing/Shuttle Material Glass Filled Nylon 6.6
Float Material Glass Filled Nylon 6.6
Glass Filled Nylon 6.6

Contact Material Ruthenium Float SG 0.74
Operating Temperature °C -30 to 130

Medium Fuels
Housing and Float Color Blue

-30 to 130 Fuels, Oils, Alcohols

Mechanical Specifications

Shock50g for 11mS durationVibration35g up to 500HzMaximum Pressure4.7 BarFloat Diameter22mm

Float Diameter 22mr IP IP65

Mounting

Cable

Cable Length

Cable Color

Connection Type Cable Type

Thread M16
Fitment Universal Internal or External
Mounting Vertical

2 x 0.5M single insulated

22 AWG 16/0.2mm PVC insulated

Stripped Cables

Black

Switching

Switch Action (Reed Switch)

Max Switching Voltage VDC

Max Switching Voltage VAC

Max Switching Current Amps

Max Switching Load Watt

Operate Mode

SPST

200


250


70

N/C with float at

Operate Mode N/C with float at bottom stop
Contact Form A

Technical Drawing





NORTH AMERICA & EUROPE

MEAS Deutschland GmbH a TE Connectivity Company Hauert 13 D-44227 Dortmund Germany Phone: +49-(0)231-9740-0 Fax: +49-(0)231-9740-20

Email: info.de@meas-spec.com

ASIA

Measurement Specialties (China), Ltd., a TE Connectivity Company No. 26 Langshan Road Shenzhen High-Tech Park (North) Nanshan District, Shenzhen 518057 China Tel +86 755 3330 5088 Fax +86 755 3330 5099

te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, MEAS, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.