


RM-Series Resin (Polyethylene) Muffler

RM-Series muffler uses rugged polyethylene housing with polyvinyl foam element. It is compact, light weight and highly effective for noise reduction without excessive back pressure. They are completely non-corrosive and highly resistant to water and oil. Elements can be easily cleaned with kerosene or similar cleaning solvent.

All models are furnished with standard male pipe threads ranging from 1/8" to 1/2" NPT; unit should be mounted in a protective position free from excessive vibration. **Hand tighten to the device only.**



SYMBOL



HOW TO ORDER

RM	—	<input type="checkbox"/>	<input type="checkbox"/>	—	<input type="checkbox"/>
Resin Muffler		Connection			Port Option
		18 = 1/8"			None = NPT
		28 = 1/4"			P = BSPT
		28L = 1/4" (high flow)			
		38 = 3/8"			
		48 = 1/2"			



California Proposition 65 Warning

WARNING: This product can expose you to chemicals, including lead, which is known to the state of California to cause Cancer, Birth Defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

SPECIFICATIONS

ITEM	MODEL	RM-18	RM-28	RM-28L	RM-38	RM-48
FLUID		AIR				
CONNECTION	NPTM	1/8"-27	1/4"-18		3/8"-18	1/2"-14
OVERALL LENGTH	IN.	1-3/8" (35mm)	1-1/2" (38mm)	2-7/16" (62mm)	2-5/8"(67mm)	2-3/4" (70mm)
DIAMETER	IN.	5/8" (16mm)	5/8" (16mm)	13/16" (20mm)	1" (26mm)	1-7/64" (28mm)
HEX	IN.	9/16" (14mm)	9/16" (14mm)	11/16" (16.8mm)	1" (24mm)	1" (24mm)
NOISE ELIMINATION EFFECT	dB	18	18	18	27	34
MATERIAL	BODY	POLYETHYLENE (PE)				
	ELEMENT	POLYVINYL FOAM (5 micron)				
MAX OPERATING PRESSURE		130 PSI (9 kg/cm ²)				
OPERATING TEMPERATURE		41° ~ 140°F (5°~60°C)				
WEIGHT (APPROX.)	OZ.	0.16	0.18	0.42	0.77	0.86
UNIT PACK	EA.	10	10	5	5	5

WARNING: Clean mufflers with neutral cleaning agent or cleaning oil, **DO NOT** use paint thinner, benzene or other organic solvents.