

Metso
EtaCrush® series
Turning Crusher ZB

Table of models and output figures



Metso Germany

E-Mail: recycling.info.de@metso.com

www.metso.com/recycling

Type	Nominal speed		Different Kinds of Turnings					Feed	
	kW	rpm	Carbon and alloyed steel turnings		Cr-Ni steel turnings / V ₂ A turnings	Aluminum alloys		From the top	From the side
			normal grid	fine grid	normal grid	normal grid	fine grid	W x L	W x H
			t/h *	t/h *	t/h *	t/h *	t/h *	mm	mm
EtaCrush® 90 x 73 ZB	37	980	2.5 - 5	1.7 - 3.5	---	0.8 - 1.4	0.6 - 1	730 x 1200	730 x 690
	55	980	3.5 - 7	2.5 - 4.5	1.4 - 2.8	1.2 - 2	0.8 - 1.5		
EtaCrush® 116 x 103 ZB	75	980	5 - 10	4 - 6	2 - 4	1.5 - 2.8	1.2 - 1.8	1030 x 890	1030 x 820
	110	980	7 - 12	5 - 8	2.8 - 4.8	2 - 4	1.5 - 2.5		
	160	980	10 - 17	7 - 11	4 - 7	2.7 - 4.6	2 - 3.4		
EtaCrush® 116 x 142 ZB	110	980	8 - 14	6 - 9	3.2 - 5.6	2 - 3.8	1.6 - 2.6	1420 x 890	1420 x 900
	160	980	11 - 20		4.4 - 8	3 - 6	2 - 3.5		
	200	980	14 - 24	10 - 15	5.6 - 9.6	3.5 - 7.5	3 - 4		

This information is only a general description and represents approximate values. It is not guaranteed and contains no warranties or assurances of any kind.

* The performance data are strongly dependent on the type and composition of the input material, the condition of the crushing tool as well as the qualification of the operator.

We reserve the right to make changes and improvements without notice, © Metso Corporation, December 2013