



LDS309-21N LDS Series-Level Sensor

Features

- High or low level sensing
- External fitting
- Reed Switch reliability
- Nitrile sealing washer
- Easy installation

Comments

- Close Differential between open and closed
- Normally open or normally closed by rotating through 180
- Suitable for a wide range of liquids
- Interface option available
- Nylon 6.6 Material

Applications

- Chemical high or low level
- Diesel Fuel
- Fuel low level
- Alcohols
- Low Oil Detection

Material

Housing MaterialGlass Filled Nylon 6.6Float MaterialGlass Filled Nylon 6.6

Contact Material Ruthenium Float SG 0.85
Operating Temperature °C -30 to 130

Medium Fuels, Oils, Alcohols

Housing and Float Color Blue

Cable

Cable Length2 x 0.5M single insulatedConnection TypeStripped Cables

Cable Type 18AWG, 32/0.2mm PVC insulated

Cable Color Black

Mechanical Specifications

Shock50g for 11mS durationVibration35g up to 500HzMaximum Pressure4.7 Bar

IP IP65

Mounting

Thread	M16	
Fitment	External	
Mounting	Horizontal	

Switching


Switch Action (Reed Switch)
Max Switching Voltage VDC
Max Switching Voltage VAC
Max Switching Current Amps
Max Switching Load Watt
Operate Mode

SPST
200
250
170
70
N/C with float horizontal

Technical Drawing

Contact Form

External Fitting



Switch operate point (DIM 'X') in water

LDS8 Polypropylene with position orientation indicator TOP 0mm with position orientation indicator BOTTOM 2mm

LDS3 Nylon 6.6 with position orientation indicator TOP 1mm with position orientation indicator Bottom 3mm

NORTH AMERICA & EUROPE

MEAS Deutschland GmbH a TE Connectivity Company Hauert 13 D-44227 Dortmund Germany Phone: +49-(0)231-9740-0 Fax: +49-(0)231-9740-20

Email: info.de@meas-spec.com

ASIA

Measurement Specialties (China), Ltd., a TE Connectivity Company No. 26 Langshan Road Shenzhen High-Tech Park (North) Nanshan District, Shenzhen 518057 China Tel +86 755 3330 5088

Fax +86 755 3330 5088

te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, MEAS, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.