


ONE-TOUCH FITTINGS

> METRIC SYSTEM

PT male branch tee




MODEL	ØD	T (Thread)	E	L	A	B	H	ØP	d	ORIFICE
PT 04-01	4	PT1/8	29.7	36.6	8	15	10	11	6.5	2.5
PT 04-02	4	PT1/4	32.7	36.6	10	15	14	11	8.7	2.5
PT 04-03	4	PT3/8	34	36.6	11	15	17	11	11.7	2.5
PT 04-M5	4	M5×P0.8	26.5	36.6	4	15	10	11	2.5	2.5
PT 04-M6	4	M6×P1.0	27	36.6	4	15	10	11	2.5	2.5
PT 06-01	6	PT1/8	30.9	37.8	8	15	12	13	6.5	2.5
PT 06-02	6	PT1/4	33.9	37.8	10	15	14	13	8.5	4
PT 06-03	6	PT3/8	35.2	37.8	11	15	17	13	11.2	4
PT 06-04	6	PT1/2	38.7	37.8	14	15	21	13	14	4.5
PT 06-M5	6	M5×P0.8	28.2	37.8	4	15	12	13	2.5	2.5
PT 06-M6	6	M6×P1.0	28.7	37.8	4	15	12	13	2.5	2.5
PT 08-01	8	PT1/8	35.4	45	8	18	14	14.4	6.8	4
PT 08-02	8	PT1/4	37.4	45	10	18	14	14.4	8.2	4
PT 08-03	8	PT3/8	38.7	45	11	18	17	14.4	11.9	4
PT 08-04	8	PT1/2	42.2	45	14	18	21	14.4	13.9	4
PT 10-01	10	PT1/8	42	55.4	8	22	17	18.4	6.5	6.5
PT 10-02	10	PT1/4	44	55.4	10	22	17	18.4	8.3	6.5
PT 10-03	10	PT3/8	45	55.4	11	22	17	18.4	11.7	6.5
PT 10-04	10	PT1/2	48.5	55.4	14	22	21	18.4	14.3	7.5
PT 12-01	12	PT1/8	44.5	59	8	22	19	21	6.5	6.5
PT 12-02	12	PT1/4	46.5	59	10	22	19	21	8	6.5
PT 12-03	12	PT3/8	48.5	59	11	22	19	21	11.5	6.5
PT 12-04	12	PT1/2	51	59	14	22	21	21	14	6.5
PT 16-03	16	PT3/8	57.5	65	11	24	24	26	11	11
PT 16-04	16	PT1/2	60.5	65	14	24	24	26	14	14

ONE-TOUCH FITTINGS

> INCH SYSTEM

PT male branch tee




MODEL	ØD	ØP	T (Thread)	L	E	A	B	H	ORIFICE
PT 5/32-UNF	5/32	11	UNF10/32	26.7	37.0	3.6	15	7/16	2.5
PT 5/32-N01	5/32	11	NPT1/8	30.3	37.0	8.5	15	7/16	3
PT 5/32-N02	5/32	11	NPT1/4	33.3	37.0	10.5	15	9/16	3
PT 3/16-UNF	3/16	13	UNF10/32	27.2	38.2	3.6	15	7/16	2
PT 3/16-N01	3/16	13	NPT1/8	30.8	38.2	8.5	15	7/16	3
PT 3/16-N02	3/16	13	NPT1/4	33.8	38.2	10.5	15	9/16	3
PT 3/16-N03	3/16	13	NPT3/8	34.8	38.2	11.5	15	11/16	3
PT 1/4-UNF	1/4	13	UNF10/32	32.4	40.8	3.6	15	1/2	2.5
PT 1/4-N01	1/4	13	NPT1/8	34.3	40.8	8.5	15	1/2	4.5
PT 1/4-N02	1/4	13	NPT1/4	37	40.8	10.5	15	9/16	4.5
PT 1/4-N03	1/4	13	NPT3/8	38	40.8	11.5	15	11/16	4.5
PT 5/16-N01	5/16	14.4	NPT1/8	36.7	43.7	8.5	18	9/16	6
PT 5/16-N02	5/16	14.4	NPT1/4	38.7	43.7	10.5	18	9/16	6
PT 5/16-N03	5/16	14.4	NPT3/8	39.7	43.7	11.5	18	11/16	6
PT 5/16-N04	5/16	14.4	NPT1/2	42.7	43.7	14.5	18	7/8	6
PT 3/8-N01	3/8	18.4	NPT1/8	38.8	47.7	8.5	22	11/16	5
PT 3/8-N02	3/8	18.4	NPT1/4	40.8	47.7	10.5	22	11/16	7
PT 3/8-N03	3/8	18.4	NPT3/8	41.8	47.7	11.5	22	11/16	7
PT 3/8-N04	3/8	18.4	NPT1/2	44.8	47.7	14.5	22	7/8	7
PT 1/2-N02	1/2	21	NPT1/4	46	56.5	10.5	22	3/4	8
PT 1/2-N03	1/2	21	NPT3/8	47	56.5	11.5	22	3/4	9
PT 1/2-N04	1/2	21	NPT1/2	50	56.5	14.5	22	7/8	9

ONE-TOUCH FITTINGS / G TYPE

> METRIC SYSTEM, BSPP, WITH INTEGRAL O-RING SEAL

PT male branch tee



MODEL	ØD	T (Thread)	L	E	A	B	H	ORIFICE
PT 04-G01	4	G 1/8	30.3	36.6	5.5	15	14	2.5
PT 04-G02	4	G 1/4	32	36.6	7.5	15	17	2.5
PT 06-G01	6	G 1/8	32.3	37.8	5.5	15	14	2.5
PT 06-G02	6	G 1/4	34.8	37.8	7.5	15	17	4
PT 06-G03	6	G 3/8	36.2	37.8	7.5	15	20	4
PT 08-G01	8	G 1/8	32.5	45	5.5	18	14	4
PT 08-G02	8	G 1/4	35.5	45	7.5	18	17	4
PT 08-G03	8	G 3/8	37.5	45	7.5	18	20	6
PT 08-G04	8	G 1/2	40	45	10	18	24	6
PT 10-G01	10	G 1/8	38.9	55.4	5.5	22	17	6
PT 10-G02	10	G 1/4	42.5	55.4	7.5	22	17	6.5
PT 10-G03	10	G 3/8	44.1	55.4	7.5	22	20	6.5
PT 10-G04	10	G 1/2	46.9	55.4	10	22	24	7.5
PT 12-G02	12	G 1/4	44.5	59	7.5	22	19	6.5
PT 12-G03	12	G 3/8	46.6	59	7.5	22	20	7
PT 12-G04	12	G 1/2	49.6	59	10	22	24	7.5
PT 16-G03	16	G 3/8	55.4	65	7.5	24	24	11
PT 16-G04	16	G 1/2	60	65	10	24	24	14